

## MANUFACTURER'S DECLARATION

### NSW PDRS Scheme - BESS1 Eligibility

From the 1<sup>st</sup> November 2024 the existing NSW Peak Demand Reduction Scheme (PDRS) will include residential battery installations (BESS 1) as an eligible technology. We hereby confirm that the following products meet the eligibility criteria for the BESS1 activity.

Model	Technical Specification	Parameter
RW-F10.2	Usable storage capacity	9.2KWh
	Ambient temperature range	-20 °C – 55 °C
	Communication interface	CAN2.0, RS485
	Control interface	N/A
	Warranty	10 years (70% usable capacity following initial installation date)
	Minimum energy throughput	32MWh

Model	Technical Specification	Parameter
RW-M6.1-B	Usable storage capacity	5.5KWh
	Ambient temperature range	-20 °C – 55 °C
	Communication interface	CAN2.0, RS485
	Control interface	N/A
	Warranty	10 years (70% usable capacity following initial installation date)
	Minimum energy throughput	20MWh

Model	Technical Specification	Parameter
AI-W5.1-B	Usable storage capacity	4.6KWh
	Ambient temperature range	-20 °C – 55 °C
	Communication interface	CAN2.0, RS485
	Control interface	N/A
	Warranty	10 years (70% usable capacity following initial installation date)
	Minimum energy throughput	16MWh

Model	Technical Specification	Parameter(Per Pack)
BOS-G	Usable storage capacity	4.6KWh
	Ambient temperature range	-10 °C – 55 °C
	Communication interface	CAN2.0, RS485
	Control interface	N/A
	Warranty	10 years (70% usable capacity following initial installation date)
	Minimum energy throughput	12.26MWh

NINGBO, 1<sup>st</sup> November 2024


  
 宁波德业储能科技有限公司
   
 NINGBO DEYE ESS TECHNOLOGY CO.,LTD